# IASEV<sup>®</sup>

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Epokoat Vernice Epossidica parte B

## 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: High performance coatings. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

Diasen S.r.I.

Zona Ind.le Berbentina, 5

60041 Sassoferrato (AN) - Marche - Italia

Phone.: +39 0732 9718 - Fax: +39 0732 971899

diasen@diasen.com https://www.diasen.com

1.4 Emergency telephone number:

#### **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1 Classification of the substance or mixture:

### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H302+H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Dam. 1: Serious eye damage, Category 1, H318 Repr. 1B: Reproductive toxicity, Category 1B, H360F Skin Corr. 1A: Skin corrosion, Category 1A, H314 Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

#### 2.2 Label elements:

## CLP Regulation (EC) No 1272/2008:

## Danger







### **Hazard statements:**

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Repr. 1B: H360F - May damage fertility.

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage Skin Sens. 1B: H317 - May cause an allergic skin reaction

### **Precautionary statements:**

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+P352: IF ON SKIN: Wash with plenty of water

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313: IF exposed or concerned: Get medical advice/attention

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

## **Supplementary information:**

EUH071: Corrosive to the respiratory tract

Contains Bisphenol A

### Substances that contribute to the classification

Benzyl alcohol; Formaldehyde, polymer with benzenamine, hydrogenated; m-phenylenebis(methylamine); 4,4´-methylenebis (cyclohexylamine)

Additional Labelling (Annex XVII, REACH):



## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 2: HAZARDS IDENTIFICATION (continued)

Restricted to professional users

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

### 3.2 Mixture:

Chemical description: Aqueous emulsion

**Components:** 

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration				
CAS: EC:	100-51-6	Benzyl alcohol□¹□	Benzyl alcohol□¹□ ATP CLP00					
Index:	202-859-9 603-057-00-5 01-2119492630-38- XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H332 - Warning	25 - <50 %				
CAS:	135108-88-2	Formaldehyde, polyr	ner with benzenamine, hydrogenated□¹□ Self-classified					
EC: Index: REACH:	Non-applicable Non-applicable I: 01-2119983522-33- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Skin Corr. 1B: H314 - Danger	25 - <50 %				
CAS:	1477-55-0	m-phenylenebis(methylamine)□¹□ Self-classified						
EC: Index: REACH:	216-032-5 Non-applicable 01-2119480150-50- XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H332; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1B: H317; EUH071 - Danger	10 - <25 %				
CAS:	1761-71-3	4,4'-methylenebis(c	yclohexylamine)□¹□ Self-classified					
EC: Index: REACH:	217-168-8 Non-applicable : 01-2119541673-38- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Chronic 2: H411; Skin Corr. 1A: H314; Skin Sens. 1: H317; STOT RE 2: H373 - Danger	2,5 - <10 %				
CAS:	80-05-7	Bisphenol A□¹□	ATP ATP09					
EC: Index: REACH:	201-245-8 604-030-00-0 01-2119457856-23- XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Repr. 1B: H360F; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	2,5 - <10 %				

<sup>□</sup>¹□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### **SECTION 4: FIRST AID MEASURES**

### 4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

## By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

## By ingestion/aspiration:

# IASEN GREEN BUILDING BUILDING

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 4: FIRST AID MEASURES (continued)

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### **SECTION 5: FIREFIGHTING MEASURES**

### 5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

## **6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

## 7.1 Precautions for safe handling:

### A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

# **IASEN**

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 7: HANDLING AND STORAGE (continued)

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits		
Bisphenol A	IOELV (8h)		2 mg/m <sup>3</sup>
CAS: 80-05-7	IOELV (STEL)		

## **DNEL (Workers):**

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
Benzyl alcohol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-51-6	Dermal	47 mg/kg	Non-applicable	9,5 mg/kg	Non-applicable
EC: 202-859-9	Inhalation	450 mg/m <sup>3</sup>	Non-applicable	90 mg/m <sup>3</sup>	Non-applicable
4,4´-methylenebis(cyclohexylamine)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1761-71-3	Dermal	Non-applicable	Non-applicable	0,1 mg/kg	Non-applicable
EC: 217-168-8	Inhalation	Non-applicable	Non-applicable	1 mg/m³	Non-applicable
Bisphenol A	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 80-05-7	Dermal	1,4 mg/kg	Non-applicable	1,4 mg/kg	Non-applicable
EC: 201-245-8	Inhalation	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

### **DNEL (General population):**

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
Benzyl alcohol	Oral	25 mg/kg	Non-applicable	5 mg/kg	Non-applicable
CAS: 100-51-6	Dermal	28,5 mg/kg	Non-applicable	5,7 mg/kg	Non-applicable
EC: 202-859-9	Inhalation	40,55 mg/m <sup>3</sup>	Non-applicable	8,11 mg/m <sup>3</sup>	Non-applicable
4,4´-methylenebis(cyclohexylamine)	Oral	Non-applicable	Non-applicable	0,06 mg/kg	Non-applicable
CAS: 1761-71-3	Dermal	Non-applicable	Non-applicable	0,06 mg/kg	Non-applicable
EC: 217-168-8	Inhalation	Non-applicable	Non-applicable	0,21 mg/m <sup>3</sup>	Non-applicable
Bisphenol A	Oral	0,05 mg/kg	Non-applicable	0,05 mg/kg	Non-applicable
CAS: 80-05-7	Dermal	0,7 mg/kg	Non-applicable	0,7 mg/kg	Non-applicable
EC: 201-245-8	Inhalation	5 mg/m³	5 mg/m <sup>3</sup>	0,25 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>



## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Benzyl alcohol	STP	39 mg/L	Fresh water	1 mg/L
CAS: 100-51-6	Soil	0,456 mg/kg	Marine water	0,1 mg/L
EC: 202-859-9	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,527 mg/kg
m-phenylenebis(methylamine)	STP	10 mg/L	Fresh water	0,094 mg/L
CAS: 1477-55-0	Soil	0,045 mg/kg	Marine water	0,0094 mg/L
EC: 216-032-5	Intermittent	0,152 mg/L	Sediment (Fresh water)	0,43 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,043 mg/kg
4,4´-methylenebis(cyclohexylamine)	STP	80 mg/L	Fresh water	0,008 mg/L
CAS: 1761-71-3	Soil	0,072 mg/kg	Marine water	0,0008 mg/L
EC: 217-168-8	Intermittent	0,08 mg/L	Sediment (Fresh water)	0,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,039 mg/kg
Bisphenol A	STP	320 mg/L	Fresh water	0,018 mg/L
CAS: 80-05-7	Soil	3,7 mg/kg	Marine water	0,016 mg/L
EC: 201-245-8	Intermittent	0,01 mg/L	Sediment (Fresh water)	2,2 mg/kg
	Oral	13,8 g/kg	Sediment (Marine water)	0,44 mg/kg

### 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

<sup>&</sup>quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

## D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

## E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	CAT III	EN 13034:2005+A1:2009 EN 168:2001 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

# IASEN<sup>®</sup>

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory foot protection	Safety footwear for protection against chemical risk	CAT III	EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
<b>=3</b> •••	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>⊢</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0 % weight
V.O.C. density at 20 °C: 0 kg/m³ (0 g/L)
Average carbon number: Non-applicable
Average molecular weight: Non-applicable

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Not available

Odour threshold:

Non-applicable \*

Volatility:

Boiling point at atmospheric pressure: 223 °C Vapour pressure at 20 °C: 5 Pa

Vapour pressure at 50 °C: 64,67 Pa (0,06 kPa)
Evaporation rate at 20 °C: Non-applicable \*

**Product description:** 

Density at 20 °C: 1063,1 kg/m<sup>3</sup>

Relative density at 20 °C: 1,063

Dynamic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 40 °C: Non-applicable \* Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* \*Not relevant due to the nature of the product, not providing information property of its hazards.

# IASEN GREEN BUILDING BUILDING

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Oxidising properties:

Non-applicable \*

Non-applicable \*

Non-applicable \*

Flammability:

Flash Point: 104 °C

Flammability (solid, gas): Non-applicable \*

Autoignition temperature: 436 °C

Lower flammability limit: Non-applicable \*
Upper flammability limit: Non-applicable \*

**Explosive:** 

Lower explosive limit:

Upper explosive limit:

Non-applicable \*

Non-applicable \*

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

## 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

## 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

## **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

## **ASEN**

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.
- B- Inhalation (acute effect):
  - Acute toxicity: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Corrosivity/Irritability: Corrosive to the respiratory tract
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
  - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Non-applicable

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: May damage fertility.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Benzyl alcohol	LD50 oral	500 mg/kg	Rat
CAS: 100-51-6	LD50 dermal	2500 mg/kg (ATEi)	
EC: 202-859-9	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Bisphenol A	LD50 oral	5100 mg/kg	Rat
CAS: 80-05-7	LD50 dermal	3000 mg/kg	Rabbit
EC: 201-245-8	LC50 inhalation	Non-applicable	
m-phenylenebis(methylamine)	LD50 oral	1090 mg/kg	Rat
CAS: 1477-55-0	LD50 dermal	Non-applicable	
EC: 216-032-5	LC50 inhalation	11 mg/L (4 h) (ATEi)	
4,4´-methylenebis(cyclohexylamine)	LD50 oral	480 mg/kg	Rat
CAS: 1761-71-3	LD50 dermal	Non-applicable	
EC: 217-168-8	LC50 inhalation	Non-applicable	
Formaldehyde, polymer with benzenamine, hydrogenated	LD50 oral	500 mg/kg (ATEi)	
CAS: 135108-88-2	LD50 dermal	Non-applicable	
EC: Non-applicable	LC50 inhalation	Non-applicable	



## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

## 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Benzyl alcohol	LC50 646 mg/L (48 h)		Leuciscus idus	Fish
CAS: 100-51-6	EC50	400 mg/L (24 h)	Daphnia magna	Crustacean
EC: 202-859-9	EC50	79 mg/L (3 h)	Scenedesmus subspicatus	Algae
m-phenylenebis(methylamine)	LC50	88 mg/L (96 h)	Oryzias latipes	Fish
CAS: 1477-55-0	EC50	15 mg/L (48 h)	Daphnia magna	Crustacean
EC: 216-032-5	EC50	20 mg/L (72 h)	Selenastrum capricornutum	Algae
4,4´-methylenebis(cyclohexylamine)	LC50	67.8 mg/L (96 h)	Leuciscus idus	Fish
CAS: 1761-71-3	EC50	2.5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 217-168-8	EC50	Non-applicable		
Bisphenol A	LC50	4.6 mg/L (96 h)	Pimephales promelas	Fish
CAS: 80-05-7	EC50	3.8 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-245-8	EC50	Non-applicable		

## 12.2 Persistence and degradability:

Identification	Identification Degradability		Biodegradability	
Benzyl alcohol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-51-6	COD	Non-applicable	Period	14 days
EC: 202-859-9	BOD5/COD	Non-applicable	% Biodegradable	94 %
m-phenylenebis(methylamine)	BOD5	Non-applicable	Concentration	14 mg/L
CAS: 1477-55-0	COD	Non-applicable	Period	28 days
EC: 216-032-5	BOD5/COD	Non-applicable	% Biodegradable	49 %
Bisphenol A	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 80-05-7	COD	Non-applicable	Period	14 days
EC: 201-245-8	BOD5/COD	Non-applicable	% Biodegradable	0 %

## 12.3 Bioaccumulative potential:

Identification	Bioaccu	Bioaccumulation potential	
Benzyl alcohol	BCF	0.3	
CAS: 100-51-6	Pow Log	1.1	
EC: 202-859-9	Potential	Low	
m-phenylenebis(methylamine)	BCF	3	
CAS: 1477-55-0	Pow Log	0.18	
EC: 216-032-5	Potential	Low	
Bisphenol A	BCF	67	
CAS: 80-05-7	Pow Log	3.32	
EC: 201-245-8	Potential	Moderate	

## 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Benzyl alcohol	Koc	Non-applicable	Henry	Non-applicable
CAS: 100-51-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 202-859-9	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Non-applicable
m-phenylenebis(methylamine)	Koc	1300	Henry	Non-applicable
CAS: 1477-55-0	Conclusion	Low	Dry soil	Non-applicable
EC: 216-032-5	Surface tension	Non-applicable	Moist soil	Non-applicable
Bisphenol A	Koc	796	Henry	1,013E-6 Pa·m³/mol
CAS: 80-05-7	Conclusion	Low	Dry soil	No
EC: 201-245-8	Surface tension	3,76E-3 N/m (364,43 °C)	Moist soil	No

### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

## 12.6 Other adverse effects:

Not described

# IASEN<sup>®</sup>

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP13 Sensitising, HP8 Corrosive

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### **SECTION 14: TRANSPORT INFORMATION**

### Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



14.1 UN number: UN3066
 14.2 UN proper shipping name: PAINT
 14.3 Transport hazard class(es): 8

 Labels: 8

 14.4 Packing group: II
 14.5 Environmental hazards: No
 14.6 Special precautions for user

Special regulations: 163, 367
Tunnel restriction code: E

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

Non-applicable

## Transport of dangerous goods by sea:

With regard to IMDG 38-16:



14.1	UN number:	UN3066
14.2	UN proper shipping name:	PAINT
14.3	Transport hazard class(es):	8
	Labels:	8
14.4	Packing group:	II
14.5	Environmental hazards:	Nο

14.5 Environmental hazards: N14.6 Special precautions for user

Special regulations: 367, 163
EmS Codes: F-A, S-B
Physico-Chemical properties: see section 9
Limited quantities: 1 L

Limited quantities: 1 L
Segregation group: Non-applicable

14.7 Transport in bulk according Non-applicable to Annex II of Marpol and

### the IBC Code: Transport of dangerous goods by air:

With regard to IATA/ICAO 2019:

# IASEV<sup>®</sup>

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN3066
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 8
Labels: 8

14.4 Packing group: II
14.5 Environmental hazards: No

**14.6 Special precautions for user** Physico-Chemical properties:

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: see section 9

Non-applicable

### **SECTION 15: REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Benzyl alcohol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Bisphenol A

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Benzyl alcohol (Product-type 6)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

### Seveso III:

Non-applicable

## Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Product classified hazardous under the CMR. Sale and distribution to the general public is prohibited. Due to its CMR category, it is essential to apply the specific measures for workplace hazard prevention covered in articles 4 and 5 of the 2004/37/EC Directive and later modifications.

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Bisphenol A. Shall not be placed on the market in thermal paper in a concentration equal to or greater than 0,02 % by weight after 2 January 2020.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

# IASEN<sup>®</sup>

## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

## **Epokoat Vernice Epossidica parte B**



## SECTION 16: OTHER INFORMATION (continued)

H314: Causes severe skin burns and eye damage

H318: Causes serious eye damage

H412: Harmful to aquatic life with long lasting effects

H317: May cause an allergic skin reaction

H360F: May damage fertility.

H302+H332: Harmful if swallowed or if inhaled

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Eye Dam. 1: H318 - Causes serious eye damage

Repr. 1B: H360F - May damage fertility.

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Skin Sens. 1: H317 - May cause an allergic skin reaction Skin Sens. 1B: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

STOT SE 3: H335 - May cause respiratory irritation

#### Classification procedure:

Skin Corr. 1A: Calculation method Eye Dam. 1: Calculation method Aquatic Chronic 3: Calculation method Skin Sens. 1B: Calculation method Repr. 1B: Calculation method Acute Tox. 4: Calculation method

## Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

## Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

## Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.