

Floorgum Antracite

Single-component, thick synthetic liquid membrane (such as **Floorgum Antracite**), formulated with water-based resins and granular aggregates, to create a base layer and obtain a cushioning effect on multi-purpose courts. Ideal for playing fields of the *TENNIS - Pro System* line. Suitable for indoor and outdoor use. Product designed for the creation of playing fields of the *TENNIS - Pro System* line in combination with the Floorgum Paint coating and the single-component liquid Colorflex coating, for the creation of the demarcation lines. The *Floorgum Antracite + Floorgum Paint* system is *ITF3 certified (International Tennis Federation - ITF)*. It is also suitable for thick application on concrete or bituminous binder substrates to even them out and prepare them for the application of coatings. On asphalt surfaces the use of a primer is not necessary. Minimum required characteristics: Break Elongation 754.60 %; Adhesion on asphalt – excellent; Adhesion on concrete 1,3 N/mm² | 188.55 lb/in²; Adhesion on bituminous membrane 1,0 MPa= N/mm² | 145.04 lb/in²; Water Vapour Permeability $\mu=655$.

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY
Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com
PARTITA IVA 01553210426 - R.E.A. Ancona n.150933
Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.

