

Floorgum Tyre Mono

Single-component, water-based, low-thickness acrylic coloured topcoat (such as **Floorgum Tyre Mono**) for multi-purpose synthetic driveway surfaces. Characterized by anti-slip properties, it has high abrasion resistance. Suitable for indoor and outdoor use. Used as a protective layer in combination with liquid waterproofing agents, it makes the surface driveable, otherwise it can be used as an alternative to traditional asphalt surfaces or other driveable coverings. The product is characterised by excellent resistance to wear, weathering, UV rays and contact with substances such as oils, fuels and smog. Minimum required characteristics: Abrasion test (Taber dry and wet test (1000 cycles)) – 0,1381% and 1,0750% of eroded material, respectively; Weathering Test – up to 1000 hours; Adhesion on system *Acriflex Fybros* waterproofing (Pull Off Test) > 7 MPa=N/mm² | 1015.26 lb/in²; Aderenza per trazione diretta 0,56 N/mm² | ; 81.22 lb/in²; Reaction to fire – Class B-s2,d0.

DIASEN srl

Zona Ind. Berbentina, 5 60041 Sassoferrato (AN) - ITALY
Tel. +39 0732 9718 - Fax +39 0732 971899 - diasen@diasen.com - www.diasen.com

PARTITA IVA 01553210426 - R.E.A. Ancona n.150933
Reg.Imp. Ancona 01553210426 - Cap. Soc. €400.000,00 i.v.

