

DECLARATION OF PERFORMANCE CPR-106/2020 DP142EN20442601

- 1. Unique identification code of the product-type: Diathonite Sismactive
- 2. Intended use/es: Designed, general purpose masonry mortar for use on walls, columns and partitions.
- 3. Manufacturer: Diasen Srl zona Ind.le Berbentina, 5 60041 Sassoferrato (AN) www.diasen.com
- 4. Systems of AVCP: System 2+.
- Harmonized standards: EN 998-2:2016
 Notified bodies: ABICert No.: 1982
- **6.** Performances declared:

| Essential characteristics | Performances |
|---|--|
| Compressive strength | M 10 |
| Compressive strength | 0,15 N/mm ² (tabulated value) |
| Flexural bond strength | NPD |
| Contents of chlorides | 0,015% |
| Reaction to fire | Class A1 |
| Water absorption | 0,30 kg/(m ² min ^{0,5}) |
| Water vapour permeability | μ = 5 |
| Thermal conductivity (λ _{10,dry}) | 0,065 W/m*K |
| Durability | NPD |
| Dangerous substances | See SDS |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Diego Mingarelli (Legal Representative)** Sassoferrato, 30/11/2020

















Zona Industriale Berbentina, 5 – 60041 Sassoferrato (AN) – Italy
www.diasen.com

20 CPR-106/2020 EN 998-2 DIATHONITE SISMACTIVE

Designed, general purpose masonry mortar for use on walls, columns and partitions

Compressive strength M 10

Compressive strength 0,15 N/mm² (tabulated value)

Flexural bond strength NPD
Contents of chlorides 0,015%

Reaction to fire Class A1

Water absorption 0,30 kg/(m²min^{0,5})

Water vapour permeability $\mu = 5$ Thermal conductivity ($\lambda_{10.drv}$): 0,065 W/m*K

Durability NPD
Dangerous substances See SDS

DIASEN supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.







